


WL 220

Boiling process



The illustration shows a similar unit

Description

■ visualisation of boiling and evaporation

Heating a liquid over a heating surface produces different modes of boiling dependent on the heat flux density. They can accelerate the evaporation process (nucleate boiling) or impair it (film boiling). In practice, a limitation of the heat flux density must be assured in order to prevent damage to the heating surface. This knowledge is applied in practice e.g. when designing steam boilers for steam-powered drives.

The WL 220 experimental unit can be used to demonstrate boiling and evaporation processes in a straightforward manner. The processes take place in a transparent tank. A condenser in the form of a water-cooled tube coil ensures a closed circuit within the tank.

R1233zd is used as evaporating liquid. Compared with water, this liquid has the advantage that its boiling point is at approx. 18°C (1013hPa), whereby the evaporation process takes place at much lower temperatures and a lower heating power.

Sensors record the flow rate of the cooling water, the heating power, pressure and temperatures at all relevant points. The measured values can be read on digital displays. At the same time, the measured values can also be transmitted directly to a PC via USB. The data acquisition software is included.

Learning objectives/experiments


- visualisation of different forms of evaporation
 - ▶ free convection boiling
 - ▶ nucleate boiling
 - ▶ film boiling
- heat transfer
- effect of temperature and pressure on the evaporation process

WL 220


Boiling process



1 safety valve, 2 displays for temperature, flow rate and pressure, 3 condenser, 4 pressure vessel, 5 drain valve for the evaporating liquid, 6 heater, 7 cooling water connection, 8 valve for adjusting the cooling water, 9 cooling water flow rate sensor



1 pressure vessel, 2 heater, 3 drain valve, 4 cooling water valve, 5 safety valve, 6 condenser; orange: evaporating liquid, red: heater, blue: cooling circuit; PSL pressure switch, E output, T temperature, Q flow rate, P pressure



Different modes of boiling: A free convection boiling, B nucleate boiling, C film boiling; red: heater, blue: evaporating liquid, white: steam, black: convection flow

Specification

- [1] visualisation of boiling and evaporation in a transparent pressure vessel
- [2] evaporation with heating element
- [3] condensation with tube coil
- [4] water supply via the lab network or via WL 110.20 Water chiller to ensure a maximum water temperature of 16°C
- [5] safety valve protects against overpressure in the system
- [6] pressure switch for additional protection of the pressure vessel, adjustable
- [7] sensors for pressure, flow rate and temperature with digital display
- [8] GUNT software for data acquisition via USB under Windows 8.1, 10
- [9] refrigerant R1233zd, GWP: 1

Technical data

Heater

- power: 250W, continuously adjustable

Safety valve: 2bar rel.

Pressure vessel: 2850mL

Condenser: coiled tube made of copper

Refrigerant

- R1233zd
- GWP: 1
- filling volume: 1,2kg
- CO₂-equivalent: 0t

Measuring ranges

- pressure: 0...4bar abs. (tank)
- power: 0...300W (heater)
- flow rate: 0,05...1,8L/min (cooling water)
- temperature: 4x 0...100°C

230V, 50Hz, 1 phase

230V, 60Hz, 1 phase

120V, 60Hz, 1 phase

UL/CSA optional

LxWxH: 1000x550x800mm

Weight: approx. 65kg

Required for operation

water connection (min. 120L/h, water temperature

max. 16°C), drain or WL 110.20

PC with Windows recommended

Scope of delivery

- 1 experimental unit
- 1 refrigerant
- 1 GUNT software + USB cable
- 1 set of hoses
- 1 set of instructional material

WL 220

Boiling process

Optional accessories

for Remote Learning

010.10000	GU 100	Web Access Box
with		
060.22000W	WL 220W	Web Access Software

Other accessories

020.30009	WP 300.09	Laboratory trolley
060.11020	WL 110.20	Water chiller